

# Celebrity® DELUXE

SUPREME PERFORMANCE,  
EXHILERATING STYLE,  
AND EXCELLENT VALUE.

## CELEBRITY® DELUXE


The **Celebrity® Deluxe** delivers superb performance and ease of use with sleek, sporty styling for an overall package that impresses with elegant simplicity. Loaded with standard features like an infinite adjustable tiller, manual recline, and dual-bulb lower light for pathway illumination, the Celebrity Deluxe is equipped to excite.



# Celebrity® Deluxe

Weight capacity:	159 kg (25 Stone)
Maximum speed <sup>1</sup> :	Up to 9.5 km/h (6.25 mph)
Ground clearance <sup>2</sup> :	10 cm (4") at shroud
Turning radius:	137 cm (54")
Overall length <sup>2</sup> :	118 cm (46.625")
Overall width <sup>2</sup> :	61 cm (24")
Front tyres:	9 cm x 25 cm (3.5" x 10")
Rear tyres:	10 cm x 25 cm (4" x 10")
Suspension:	Front and Rear
Range per charge <sup>1,5</sup> :	Up to 23.43 km (14.56 miles) with 45 AH batteries
Maximum obstacle climbing ability:	9.5 cm (3.75")
Total Weight Without Batteries:	88.67 kg (195.5 lbs.)
Heaviest piece when disassembled:	29.5 kg (65 lbs.) Front section
Standard seating:	Type: CRS Deluxe Weight: 23 kg (51 lbs.) Material: Black Vinyl Dimensions: width – 46 cm (18") depth – 46 cm (18")
Drive System:	Rear-wheel drive, sealed transaxle, 24-volt DC motor
Dual Braking System:	Regenerative, and electromechanical
Battery Requirements <sup>3</sup> :	Two 12-volt, deep cycle Size: 30 amp or optional 40 amp Weight <sup>4</sup> : <b>30 AH:</b> 11 kg (24.5 lbs.) each; <b>40 AH:</b> 15 kg (33 lbs.) each
Battery Charger:	5-amp, off-board

Colours:



<sup>1</sup>Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tyre condition.

<sup>2</sup>Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).

<sup>3</sup>AGM or Gel-Cell type required.

<sup>4</sup>Battery weight may vary based on manufacturer.

<sup>5</sup>Tested in accordance with ASNI/RESNA, WC Vol 2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculation based on battery specifications and drive system performance. Test conducted at maximum weight capacity.

NOTE: All specifications subject to change without notice.

The information contained herein is correct at the time of publication; due to the manufacturers commitment to constant improvement and development, they reserve the right to alter specifications without prior notice. Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressure, ambient temperature, and the gradient and surface of the road or pavement.

## Features

- Front and rear suspension
- Maximum speed up to 9.5 km/h (6.25 mph)
- Maximum weight capacity of 159 kg (25 Stone)
- Ultra-simple, auto-latching lock-up for quick disassembly/reassembly
- Easily accessible tie down points (for transport of unoccupied scooter)
- Front basket standard
- Tight turning radius of 137 cm (54")
- Includes standard angle-adjustable dual bulb kerb light
- Front frame-mounted seat post for optimal stability
- High visibility reflectors
- Microprocessor based controller
- Tiller rotation lock permits tiller to be used as handle during transport

## Options

- Cane/crutch holder
- Oxygen tank holder
- Rear basket
- Walker holder
- Upgrade to 40 amp batteries